

# SealPRO<sup>TM</sup>

## DRY FIX

Leak Proof Solution For Roof Ridges & Hips



### LEAK PROOF SOLUTION FOR ROOF RIDGES & HIPS

- ✓ 100% LEAK PROOF
- ✓ EASY & FAST INSTALLATION
- ✓ NEAT & GOOD LOOKING SOLUTION FOR RIDGES & HIPS
- ✓ AVAILABLE MATCHING COLORS THAT COMPLEMENTS YOUR TILES



**PERFORMANCE**  
**100% LEAK PROOF**  
Complete peace of mind  
Long-lasting water-tightness



**AESTHETICS**  
More enduring and tidy  
finishing compared to  
traditional mortar



**FAST INSTALLATION**  
Saves time because no  
drying time for cement  
mortar is required.



**EASE OF USE**  
Easy to apply to any  
surface due to it's  
flexibility

## PRODUCT DESCRIPTION

**SealPRO™ DRY FIX** is a waterproof dry fix solution specifically designed to replace traditional cement mortar for roof ridges and hips, offering a beautiful finishing with high durability and excellent water-tightness against driving rain. Its flexible and UV-stabilized surface is lightweight and self-fixing onto dust-free surfaces with adhesive bitumen compound, safely protecting the ridge and hip against rainwater entry.

## PRODUCT DATA

Material	Aluminium composite on top with flexible bitumen adhesive compound and single layer of PE film
Thickness	1.5mm including the release PE Film
Colours	Maroon, Natural and Black
Length of Roll	10m
Width of Roll	300mm



**Traditional Cement Mortar Method**



**SealPRO™ DRY FIX Method**

Recommended Specifications:

**SealPRO™ DRY FIX** leak-proof solution for roof ridges and hips to be installed in accordance with **SealPRO™** recommended installation guide.

## INSTALLATION GUIDE



**Step 1:** Cut the tiles along the hip tree with a gap about 5mm.



**Step 2:** Choose a matching metal finishing colour and unroll the required length.



**Step 3:** Remove the release film and place in position.



**Step 4:** Press to the profile of the tiles and make sure all gaps are sealed.



**Step 5:** Fix the hips tiles in place and nail to the hip tree. Make sure the membrane is hidden and not exposed under the ridge/hip tiles.



**Step 6:** Place all the hip tiles, meanwhile the installation of SealPRO™ DRY FIX is completed.

Please refer to product data and safety data sheets for full instructions and precautions in use or for specific advice, contact SealPRO Technical Services Department.